





True side



1st, 5-6 sec
2nd, 15 sec



150°C
(302 F)



1st. 200 g/cm²
2nd. 350-400 g/cm²



Silver
gritter



630mm
×20M roll



The universal Gritter Printable Cutting Sheet

- ☆ No need to stock a variety of color for the gritters. Print whatever the colors needed.
- ☆ Get metallic expressions without using metallic ink.
- ☆ Metallic but stretchable. Good for light water repellent / proof materials too.
- ☆ Able to be printed by UV printing & screen printing.

Transfer Conditions

1st, heat press ※ "Application sheet must be used for SP-JMG."

Temperature	Time	Pressure
150°C	5-6 sec	200g/ cm ²

Peel off the Application sheet while hot.

2nd, heat press ※ Apply kraft paper on the sheet to press.

Temperature	Time	Pressure
150°C	15 sec	350~400g/ cm ²

※ Adjustment of temperature and pressure is required depending on the material.

※ Stronger adhesion is obtained by pressing the transferring surface against the lower plate of the press machine at 2nd transfer process.



Material / Fabric selection

Cotton	Polyester	Sublimated poly	Blends	Nylon	Weak water repellent
○	○	○	○	○	○

Dimensions

1 roll : 630mm × 20M

※ Always apply kraft paper at pressing after application sheet was removed.

※ Cover the transferred area with a cloth when ironing to avoid direct contact.

※ We highly recommend that before every usage a test should be conducted on the original material.

Materila

Polyurethane 100%

Japanese Industrial Standard (JIS) :L 103 5 class

Test methods for colour fastness to dry cleaning (petroleum) 5 class. (JIS - L 0860) / Test methods for colour fastness to rubbing 4~5 class. (JIS - L 0849)

Test result : Test methods for colour fastness to bleaching with hypochlorite 5 class. (JIS - L 0856)

Formalin max 0.01 (Can be used for baby clothes within 24 months of age.)